




Wallchart System























Long Lasting
Beauty

Clean Print

Anniversary Program



Hard Floor Cleaning Program

| ROUTINE | RESTORATION |
|--|---|
|  <p>AUTO SCRUB OR DAMP MOP CLEANING</p>     <p>AUTO SCRUB CLEANING 1. DUST MOP the floor before applying cleaner. 2. DILUTE: Mix product according to label directions. 3. CLEAN: Scrub with red pad. Apply cleaning solution, scrub and pick up in one operation. Rinsing not required. 4. PICK UP TRAILS: Use clean water and mop/bucket to pick up any trails left from autoscrubber.</p> <p>DAMP MOP CLEANING 1. DUST MOP the floor before applying cleaner. 2. DILUTE: Mix product according to label directions. 3. CLEAN: Using a clean mop, damp mop the floor. Change the cleaning solution frequently. No rinse required.</p> |  <p>AUTO SCRUB OR DAMP MOP CLEANING</p>     <p>AUTO SCRUB CLEANING 1. DUST MOP the floor before applying cleaner. 2. DILUTE product according to label directions. 3. APPLY solution and scrub with a red or white pad. 4. BURNISH the floor when the solution is thoroughly dry to "pop the gloss".</p> <p>DAMP MOP CLEANING 1. DUST MOP the floor before applying cleaner. 2. DILUTE product according to label directions. 3. APPLY solution to floor. Change solution when it becomes dirty. No rinsing required. 4. BURNISH the floor when the solution is thoroughly dry to "pop the gloss".</p> |
| SCRUB & RECOAT | STRIPPING & FINISHING |
|  <p>SCRUB & RECOAT</p>       <p>1. DUST MOP the floor. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife. 2. DAMP MOP or AUTOSCRUB using Fuller Cleaner and following the label directions. 3. APPLY a coat of Fuller Finish a clean mop. 4. DRY Allow 20-30 minutes drying time. 5. APPLY 2 coats. For best results allow adequate drying time between each coat. 6. BURNISH optional burnishing after last coat - wait 1 hour.</p> |  <p>STRIPPING AND FINISHING</p>         <p>1. DILUTE product according to label directions. 2. APPLY the diluted solution liberally with a mop on a small section. 3. SCRUB the floor using a rotary machine and a black pad. 4. REMOVE the remaining solution off the floor using a mop or wet vacuum. 5. RINSE the floor with clean water and remove using a mop or wet vacuum. 6. APPLY 2 coats of Fuller Sealer a clean mop. 7. DRY Allow 20-30 minutes drying time between coats. 8. APPLY 4 coats of Fuller Finish. For best results allow adequate drying time between each coat. 9. BURNISH after last coat - wait 1 hour. (optional)</p> |



Distributed By:

MSDS Fax Retrieval: **800-551-0101** CHEMTREC Day or Night: **800-424-9300**
 TECH HOTLINE: **800-810-4829**

ORDER CODE: GEN-010

PRODUCT SELECTION

Cleaner - Concur
 Finish - Anniverasry
 Sealer - Fullprime

Maintainer - Appearance Plus
 Stripper - Vanqish
 S+R Cleaner - Fullscrub

Long Lasting
Beauty

Clean Print

Appearance Program



Hard Floor Cleaning Program

ROUTINE



CONCUR

AUTO SCRUB OR DAMP MOP CLEANING



CAUTION 1. DUST MOP 2. DILUTE 3. CLEAN 4. PICK UP



OR 2. DILUTE 3. CLEAN

AUTO SCRUB CLEANING
 1. DUST MOP the floor before applying cleaner.
 2. DILUTE: Mix product according to label directions.
 3. CLEAN: Scrub with red pad. Apply cleaning solution, scrub and pick up in one operation. Rinsing not required.
 4. PICK UP TRAILS: Use clean water and mop/bucket to pick up any trails left from auto-scrubber.

DAMP MOP CLEANING
 1. DUST MOP the floor before applying cleaner.
 2. DILUTE: Mix product according to label directions.
 3. CLEAN: Using a clean mop, damp mop the floor. Change the cleaning solution frequently. No rinse required.

RESTORATION



APPEARANCE

AUTO SCRUB OR DAMP MOP CLEANING



CAUTION 1. DUST MOP 2. PLACE 3. APPLY 4. BURNISH



OR 2. DILUTE 3. APPLY 4. BURNISH

AUTO SCRUB CLEANING
 1. DUST MOP the floor before applying cleaner.
 2. DILUTE: Mix product according to label directions.
 3. APPLY: solution and scrub with a red or white pad. Scrape up excess solution from floor.
 4. BURNISH the floor when the solution is thoroughly dry to "pop the gloss".

DAMP MOP CLEANING
 1. DUST MOP the floor before applying cleaner.
 2. DILUTE: Mix product according to label directions.
 3. APPLY: solution to floor. Change solution when it becomes dirty. No rinsing required.
 4. BURNISH the floor when the solution is thoroughly dry to "pop the gloss".


SCRUB & RECOAT




SCRUB & RECOAT



CAUTION 1. DUST MOP 2. DAMP MOP 3. APPLY 4. DRY



5. APPLY 6. BURNISH

1. DUST MOP the floor. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife.
2. DAMP MOP or AUTOSCRUB using Fuller Cleaner and following the label directions.
3. APPLY a coat of Fuller Finish a clean mop.
4. DRY Allow 20-30 minutes drying time.
5. APPLY 2 coats. For best results allow adequate drying time between each coat.
6. BURNISH optional burnishing after last coat - wait 1 hour.

STRIPPING & FINISHING






STRIPPING AND FINISHING



CAUTION 1. DILUTE 2. APPLY 3. SCRUB 4. REMOVE



5. RINSE 6. APPLY 7. DRY 8. BURNISH

1. DILUTE product according to label directions.
2. APPLY the diluted solution liberally with a mop on a small section.
3. SCRUB the floor using a rotary machine and a black pad.
4. REMOVE the remaining solution off the floor using a mop or wet vacuum.
5. RINSE the floor with clean water and remove using a mop or wet vacuum.
6. APPLY 2 coats of Fuller Sealer a clean mop.
7. DRY Allow 20-30 minutes drying time between coats.
8. APPLY 4 coats of Fuller Finish. For best results allow adequate drying time between each coat.
9. BURNISH after last coat - wait 1 hour (optional)



Distributed By:

MSDS Fax Retrieval: **800-551-0101**
 CHEMTREC Day or Night: **800-424-9300**
 TECH HOTLINE: **800-810-4829**

ORDER CODE: GEN-011

PRODUCT SELECTION

Cleaner - Concur Maintainer - Appear. Auto/ Burnish
Finish - Appearance Stripper - Vanquish
Sealer - Appear. Sealer/Finish S+R Cleaner - Fullscrub

Wet Look
Shine

Appearance 2000 Program

Clean Print



Hard Floor Cleaning Program

ROUTINE



AUTO SCRUB OR DAMP MOP CLEANING



- AUTO SCRUB CLEANING**
1. DUST MOP the floor before applying cleaner.
 2. DILUTE: Mix product according to label directions.
 3. CLEAN: Scrub with red pad. Apply cleaning solution, scrub and pick up in one operation. Rinse mop.
 4. PICK UP TRAILS: Use clean water and mop/bucket to pick up any trails left from auto-scrubber.
- DAMP MOP CLEANING**
1. DUST MOP the floor before applying cleaner.
 2. DILUTE: Mix product according to label directions.
 3. CLEAN: Using a clean mop, damp mop the floor. Change the cleaning solution frequently. No rinse required.

RESTORATION



AUTO SCRUB OR DAMP MOP CLEANING



- AUTO SCRUB CLEANING**
1. DUST MOP the floor before applying cleaner.
 2. DILUTE product according to label directions.
 3. APPLY solution and scrub with a red or white pad. Vacuum up excess solution from floor.
 4. BURNISH the floor when the solution is thoroughly dry to "pop the gloss".
- DAMP MOP CLEANING**
1. DUST MOP the floor before applying cleaner.
 2. DILUTE product according to label directions.
 3. APPLY solution to floor. Change solution when it becomes dirty. No rinsing required.
 4. BURNISH the floor when the solution is thoroughly dry to "pop the gloss".

SCRUB & RECOAT



- SCRUB & RECOAT**
1. DUST MOP the floor. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife.
 2. DAMP MOP or AUTOSCRUB using Fuller Cleaner and following the label directions.
 3. APPLY a coat of Fuller Finish a clean mop.
 4. DRY Allow 20-30 minutes drying time.
 5. APPLY 2 coats. For best results allow adequate drying time between each coat.
 6. BURNISH optional burnishing after last coat - wait 1 hour.

STRIPPING & FINISHING



STRIPPING AND FINISHING



- STRIPPING AND FINISHING**
1. DILUTE product according to label directions.
 2. APPLY the diluted solution liberally with a mop on a small section.
 3. SCRUB the floor using a rotary machine and a black pad.
 4. REMOVE the remaining solution off the floor using a mop or wet vacuum.
 5. RINSE the floor with clean water and remove using a mop or wet vacuum.
 6. APPLY 2 coats of Fuller Sealer a clean mop.
 7. DRY Allow 20-30 minutes drying time between coats.
 8. APPLY 4 coats of Fuller Finish. For best results allow adequate drying time between each coat.
 9. BURNISH after last coat - wait 1 hour. (optional)



Distributed By:

MSDS Fax Retrieval: 800-551-0101
CHEMTREC Day or Night: 800-424-9300
TECH HOTLINE: 800-810-4829

ORDER CODE: GEN-012

PRODUCT SELECTION

Cleaner - Concur Maintainer - Appear. Auto/Burnish
Finish - Appearance 2000 Stripper - Vanquish
Sealer - Appear. Sealer/Finish S+R Cleaner - Fullscrub

Durable
High Gloss

Clean Print

Radiant Program



Hard Floor Cleaning Program

ROUTINE



AUTO SCRUB OR DAMP MOP CLEANING



- AUTO SCRUB CLEANING**
1. **DUST MOP** the floor before applying cleaner.
 2. **DILUTE** Mix product according to label directions.
 3. **CLEAN** Scrub with red pad. Apply cleaning solution, scrub and pick up in one operation. Rinsing not required.
 4. **PICK UP TRAILS:** Use clean water and mop/bucket to pick up any trails left from autoscrubber.
- DAMP MOP CLEANING**
1. **DUST MOP** the floor before applying cleaner.
 2. **DILUTE** Mix product according to label directions.
 3. **CLEAN:** Using a clean mop, damp mop the floor. Change the cleaning solution frequently. No rinse required.

RESTORATION



AUTO SCRUB OR DAMP MOP CLEANING




- AUTO SCRUB CLEANING**
1. **DUST MOP** the floor before applying cleaner.
 2. **DILUTE** product according to label directions.
 3. **APPLY** solution and scrub with a red or white pad. Scrape up excess solution from floor.
 4. **BURNISH** the floor when the solution is thoroughly dry to "pop the gloss".
- DAMP MOP CLEANING**
1. **DUST MOP** the floor before applying cleaner.
 2. **DILUTE** product according to label directions.
 3. **APPLY** solution to floor. Change solution when it becomes dirty. No rinsing required.
 4. **BURNISH** the floor when the solution is thoroughly dry to "pop the gloss".

SCRUB & RECOAT



SCRUB & RECOAT



1. **DUST MOP** the floor. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife.
2. **DAMP MOP or AUTOSCRUB** using Fuller Cleaner and following the label directions.
3. **APPLY** a coat of Fuller Finish a clean mop.
4. **DRY** Allow 20-30 minutes drying time.
5. **APPLY** 2 coats. For best results allow adequate drying time between each coat.
6. **BURNISH** optional burnishing after last coat - wait 1 hour.

STRIPPING & FINISHING



STRIPPING AND FINISHING



1. **DILUTE** product according to label directions.
2. **APPLY** the diluted solution liberally with a mop on a small section.
3. **SCRUB** the floor using a rotary machine and a black pad.
4. **REMOVE** the remaining solution off the floor using a mop or wet vacuum.
5. **RINSE** the floor with clean water and remove using a mop or wet vacuum.
6. **APPLY** 2 coats of Fuller Sealer a clean mop.
7. **DRY** Allow 20-30 minutes drying time between coats.
8. **APPLY** 4 coats of Fuller Finish. For best results allow adequate drying time between each coat.
9. **BURNISH** after last coat - wait 1 hour (optional).



Distributed By:

MSDS Fax Retrieval: **800-551-0101** CHEMTREC Day or Night: **800-424-9300**
TECH HOTLINE: **800-810-4829**

ORDER CODE: GEN-013


PRODUCT SELECTION

Cleaner - Concur Maintainer - Appear. Auto/Burnish
Finish - Radiant Stripper - Vanquish
Sealer - Appear. Sealer/Finish S+R Cleaner - Fullscrub

Professional Quality



Clean Print

Restroom Program




Restroom Cleaning Program

MIRRORS & SINKS





MIRRORS



1. SPRAY 2. WIPE

SINKS & FAUCETS




1. SPRAY 2. WIPE


1. **SPRAY** on sparingly using a fine to medium spray.
2. **WIPE** immediately with a clean soft cloth in the direction of the grain.

1. **SPRAY** on sparingly using a fine to medium spray.
2. **WIPE** immediately with a clean soft cloth in the direction of the grain.

TILE SURFACES AND FLOORS




TILE SURFACES



1. APPLY 2. WAIT

FLOORS





1. APPLY 2. WAIT


1. **APPLY** solution to tile surfaces, wetting surfaces thoroughly.
2. **WAIT:** Treated surfaces must remain wet for 10 minutes. Rinse or let air dry.

1. **APPLY** solution to floors, wetting surfaces thoroughly.
2. **WAIT:** Treated surfaces must remain wet for 10 minutes.

TOILETS AND URINALS

TOILETS AND URINALS





1. APPLY 2. SWAB 3. SCRUB 4. WAIT


1. **APPLY:** Spray the exposed surfaces of toilet or urinal.
2. **SWAB** the area with sponge or brush.
3. **SCRUB** thoroughly the interior of the bowl or urinal using a brush.
4. **WAIT:** Let stand for 10 minutes, then flush.

Weekly - use Spray 'n Dissolve to clean toilets and urinals

SHOWER ROOMS





DAILY (Fullsan)



1. DILUTE 2. APPLY 3. WAIT


WEEKLY (Fullpower)



1. DILUTE 2. APPLY 3. WAIT 4. SCRUB 5. RINSE

1. **DILUTE:** Mix product according to label directions.
2. **APPLY:** solution to tile surfaces, wetting surfaces thoroughly.
3. **WAIT:** Treated surfaces must remain wet for 10 minutes. Rinse or let air dry.

1. **DILUTE:** Mix product according to label directions.
2. **APPLY:** liberally with a spray bottle or sponge.
3. **WAIT:** 2 to 5 minutes for cleaner to work.
4. **SCRUB:** If film is heavy, scrub with a brush or scrubber pad.
5. **RINSE:** well with clear water.



Distributed By:

MSDS Fax Retrieval: **800-551-0101** CHEMTREC Day or Night: **800-424-9300**

TECH HOTLINE: **800-810-4829**

ORDER CODE: GEN-014

PRODUCT SELECTION

Full Sparkle

Fullsan


Fullpower

Spray 'n Dissolve

Professional Quality


Clean Print

Office Area Program




Office Area Cleaning Program


GLASS, WINDOWS AND MIRRORS




GLASS




1. DILUTE: Mix product according to label directions.
2. SPRAY on sparingly using a fine to medium spray.
3. WIPE immediately with a clean soft cloth.




WINDOWS



1. DILUTE: Mix product according to label directions.
2. SPRAY on sparingly using a fine to medium spray.
3. WIPE immediately with a clean soft cloth.
4. SQUEEGEE immediately in a downward motion wiping the squeegee after each pass.




MIRRORS




1. DILUTE: Mix product according to label directions.
2. SPRAY on sparingly using a fine to medium spray.
3. WIPE immediately with a clean soft cloth.


DESKS, COUNTERS AND TABLES



CLEANING



1. DILUTE: Mix product according to label directions.
2. APPLY solution to desks, counters and tables thoroughly wetting surfaces as recommended and required.
3. WAIT: Treated surfaces must remain wet for 10 minutes.
4. WIPE or let air dry.



Distributed By:

MSDS Fax Retrieval: **800-551-0101** CHEMTREC Day or Night: **800-424-9300**

TECH HOTLINE: **800-810-4829**

ORDER CODE: GEN-015


PRODUCT SELECTION

**Fullsparkle
Fullsan**

Dilution
Control

Restroom Program

FULLER BRUSH COMMERCIAL Restroom Cleaning Procedure



READ and FOLLOW all label directions before using products.



1 FULLSPARKLE



Cleans and polishes all mirrors, chrome and hard surfaces.

Use Areas:
Mirrors, Sinks, Hand Dryers,
General Chrome Surfaces
and General Hard Surfaces



2 SPRAY 'n DISSOLVE



Ready-to-use soap scum and rust stain remover.

Use Areas:
Sinks, Tile, Porcelain Surfaces,
Baseboard and Grout.



3 FULLSAN



EPA Registered product that disinfects and deodorizes hard surfaces in one easy step.

Use Areas:
Toilets and Urinals, Daily use on Walls,
Floors and Hard Non-Porous Surfaces.



4 FULLPOWER



Heavy duty foaming cleaner, effectively penetrates and lifts soil and soap scum.

Use Areas:
Floors, Sinks, Walls, and
Hard Non-Porous Surfaces.



5 PORCELAIN AND TILE CLEANER



Ready-to-use soap scum and rust stain remover.

Use Areas:
Sinks, Tile, Porcelain Surfaces,
Baseboard and Grout.



Distributed By:

MSDS Fax Retrieval:
800-551-0101

CHEMTREC Day or Night:
800-424-9300

TECH HOTLINE:
800-810-4829

GEN-016

ORDER CODE: GEN-016

PRODUCT SELECTION

Fullsparkle

Spray 'n Dissolve

Fullsan


Fullpower

Porcelain and Tile Cleaner

*Dilution
Control*

Restroom Program

FULLER BRUSH COMMERCIAL Restroom Cleaning Procedure



READ and FOLLOW all label directions before using products.



1 FULLSPARKLE



Cleans and polishes all mirrors, chrome and hard surfaces.

Use Areas:
Mirrors, Sinks, Hand Dryers, General Chrome Surfaces and General Hard Surfaces



2 SPRAY 'n DISSOLVE



Ready-to-use soap scum and rust stain remover.

Use Areas:
Sinks, Tile, Porcelain Surfaces, Baseboard and Grout.



3 FULLSAN



EPA Registered product that disinfects and deodorizes hard surfaces in one easy step.

Use Areas:
Toilets and Urinals, Daily use on Walls, Floors and Hard Non-Porous Surfaces.



4 FULLPOWER



Heavy duty foaming cleaner, effectively penetrates and lifts soil and soap scum.

Use Areas:
Floors, Sinks, Walls, and Hard Non-Porous Surfaces.



5 PORCELAIN AND TILE CLEANER



Ready-to-use soap scum and rust stain remover.

Use Areas:
Sinks, Tile, Porcelain Surfaces, Baseboard and Grout.



Distributed By:

MSDS Fax Retrieval:
800-551-0101

CHEMTREC Day or Night:
800-424-9300

TECH HOTLINE:
800-810-4829

GEN-016

Clean Print

ORDER CODE: GEN-017

PRODUCT SELECTION

Fullsparkle

Spray 'n Dissolve

Fullsan

Fullpower

Porcelain and Tile Cleaner